

MC-24 High-speed centrifuge

Centrifuge

Introduction

MC-24 high-speed centrifuge is widely used in life science, biology, molecular biology, physical and chemical analysis and other fields, for the separation of cells, proteins, virus samples, etc. The maximum speed can reach 15000rpm.

Characteristics:

1. High-speed and stable operation, the rotor and the motor shaft are matched with high-precision cones, high concentricity, and low operating noise.
2. Both the upper cover and the lower shell adopt high-strength metal protective rings, which have high structural safety and ensure the safe operation of the rotor at high speed.
3. The invention patent of the upper cover safety lock ensures the safety during operation. It automatically pops up after the operation is completed, and has one-key open cover function.
4. Adopting the three-dimensional air inlet circulation cooling method, the cooling effect is good, and the temperature rise of the rotor is low.
5. Powerful DC brushless motor, maintenance-free, fast drive, ultra-quiet operation, low noise level.
6. After the centrifugation is finished, the sound prompts and the cover will automatically opened, which is convenient for the sample to cool down; the brake is soft to protect the special sensitive samples.
7. The speed up/down speed is adjustable, suitable for different experimental requirements.
8. It adopts 4.3-inch color LCD screen, which can display the speed, centrifugal force and time at the same time.
9. The buzzer prompts after the operation is completed, with the function of displaying the running status and prompting the error code.
10. With PROG key, you can call the built-in 10 groups of programs with one key, which is convenient and quick to use.
11. Equipped with a momentary centrifugal button, which can be centrifuged quickly to meet more experimental needs.
12. High-strength aluminum alloy rotor has no service life limit and can be sterilized by high temperature and high pressure.
13. One machine for multiple purposes, suitable for 0.2, 0.5, 1.5, 2.0, 5.0ml centrifuge tubes and PCR centrifuge tubes, four rotors are available.

Accessories



MC-A: 5mlx18
Max. speed:15000rpm
Max. RCF: 21400xg



MC-B: 0.2mlx32
0.2mlx8 stripx4
Max. speed:15000rpm
Max. RCF:17624xg



MC-C: 0.5mlx36
Max. speed:15000rpm
Max. RCF:21400xg



MC-D: 0.2ml/0.5ml/1.5ml/2mlx24
Max. speed:15000rpm
Max. RCF:21400xg



MC-D-1: 2ml to 0.2ml test tube set
MC-D-2: 2ml to 0.2ml test tube set



Technical parameter

Model	MC-24	Working noise	≤62 dB
Speed range	500–15000rpm (increment: 100rpm)	Safety	High-strength metal protective ring, safety door lock, overspeed, overtemperature, status diagnosis
Time range	1s–99min59s (can be centrifuged instantly)		
Speed up down time range	25 or 45s (to protect special sensitive samples from resuspension)	Other functions	Speed/acceleration display function, instantaneous centrifugal function, running progress display, sound prompt function
Rotor capacity	0.2ml/0.5ml/1.5ml/2mlx24;	Voltage	AC 220V 50Hz
	0.2mlx8 stripx4; 0.5mlx36; 5mlx18;	Max. power	500W
Max. RCF	21400xg	Fuse	250V ,15A, φ5×20
Temp. range	-20°C to +40°C	Dimensions (W x D x H)	W.238XD.335XH.208mm
Temp.control accuracy (at 4°C)	±2°C	Net weight	13kg
Time from R. T. to 4°C	≤8min		